



Tiger 1200 Explorer Pannier Rack

Installation Guide

A qualified, experienced motorcycle technician should install Rockfox products. If you are unsure of your ability to properly install a product, please have the product installed by your local motorcycle dealer. Rockfox takes no responsibility for damages caused by improper installation. All screws, bolts and nuts, including all replacement hardware provided by Rockfox, should be tightened to the torque specified in the OEM maintenance manual for your motorcycle. If no torque specifications are provided in the OEM maintenance manual, the following torques may be used: M6 – 9,6Nm; M8 – 23Nm; M10 – 46Nm. All screws, bolts and nuts should be checked after driving the first 50 km to ensure that all are tightened to the proper torque. Medium strength liquid thread-locker (i.e., "Loctite") should be used to secure all screws bolts and nuts.

Tools required: 8mm Allen key
13mm Spanner

Contents: 1 x Left Side Rack
1 x Right Side Rack
1 x Rear Brace
2 x Aluminium Spacers

Right Side

Step 1



Remove the rear footpegs.

Step 2



Remove the bolts from the rear of the seat

Step 3



Attach the Right hand Pannier frame to the bike frame

****Do not Tighten any bolts yet****

Step 4



Attach the front bracket of the pannier frame behind the rear footpeg.using the bolts supplied.

Step 5



insert the provided aluminium spacer the the front of the rear footpeg with the supplied bolts.

Repeat Step 1, 2, 3, 4 and 5 for the left hand side.

Step 6



Attach the rear brace between the two racks with the supplied bolts and nuts.

Step 7

Tighten all bolts.

Final product



Please contact us if you encounter any problems

Regards
The Rockfox Team